

Public Address Audio System—Wireless microphone Series



With prelude prompt tone

SM-88 CM-38

Conference gooseneck microphone

- ◆ Model No.: SM-88/CM-38
- ◆ Type of Adapter: Capacitive
- ◆ Frequency Range: 40Hz-16KHz
- ◆ Directivity: Cardioid
- ◆ Output impedance: 200Ω
- ◆ S.P.L: -42dB±2
- ◆ Power supply: DC3V
- ◆ Mic cable length: standard 500CM



V
band

OK-2600



U
band

OK-2600A

Wireless Microphone

1. Reception performance

Reception performance: Quartz crystal controls the locking frequency

Receiver S.P.L:60dbs(12dBu)

SNR:>100dB

Audio output level: CHA+ imbalance 0-0.5V/5KΩ

The CHA and CHB are unbalanced from 0 to 0.5V/5 Kω

Size:20(L)x 240(W)×45(H)mm

2. Transmitter performance

RF Power:30mW(Max)

Suppression :> Carrier 45dB

Antenna: Completely hidden

Microphone: moving coil type super heart type single directional

Battery: Standard 9V battery

Battery consumption: About 25mA

Battery life: more than 8 hours of continuous use

Size:52(D) x247(L)m/m

Weight: About 227gs

3. System indicators

Frequency range :VHF high band 220-270MHz

Frequency stability :0.005%

Modulation mode :FM

Maximum frequency offset: ±15KHZ

Audio response :40HZ-20KHZ

SNR:100dB

Dynamic range :100dB

Comprehensive distortion :≤0.5%

Operating range :50 m radius (when there is no obstacle)

Operating temperature :-10°C-50°C

Public Address Audio System—Volume Controller



Regular 5 levels volume controller (White)

YV-6-6W
YV-10-10W
YV-30-30W
YV-60-60W



5 levels volume controller (Space black)

HS-6-6W
HS-10-10W
HS-30-30W
HS60-60W

Knob



5 levels volume controller (Gold)

JS-6-6W
JS-10-10W
JS-30-30W
JS-60-60W

knob



Stepless Volume Controller

WJ-6-6W
WJ-10-10W
WJ-30-30W
WJ-60-60W

Stepless