



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace [FreeWorldImports.com](https://freeworldimports.com)

FREEWORLD FEATURED & SPECIAL DEALS COMMODITIES | EQUIPMENT | PRODUCTS

UAV & REMOTE TECHNOLOGY SOLUTIONS (GIMBALS | PODS | AUTONOMOUS DRONES)

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | **Liquidation Marketplace:** <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | **Email:** bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace [FreeWorldImports.com](https://freeworldimports.com)

TRANSACTION / DEAL STRUCTURE

- *Branded Merchandise below wholesale price*
- *Available for Immediate Delivery – EXW Factory - (Asia) | DDP, USA*
- *Customer Branding is available*
- **MOQ:** *1 – 500 Units – (Models and Combination) | Per Customer Requirement*

Interested parties are encouraged to contact us via email: bizdev@freeworldbrand.com for pricing and other related information.

PRODUCT RELATED IMAGES AND OTHER RELATED INFORMATION APPEAR ON THE FOLLOWING PAGES

Information related to this product | solution to include:

- **Product Description & Specifications**
- **Images**

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace FreeWorldImports.com



309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



Z-9B

Intelligent Multi-sensor Gimbal

- AI Multi-object Detection & Tracking
- 120x Zoom
- Thermal 640x512 25mm
- Laser Ranging 1800m
- Laser Lighting

MAVLINK
QGroundControl

173x144x206mm
The Size Of The Whole Machine

1158g
Total Weight

360°xN
Yaw Axis Spins Continually

3-axis Mechanical Stabilization



General			
Dimensions	173 x 144 x 206mm		
Weight	1158g		
Operating Voltage	20 ~ 53 VDC		
Power	21.4W (AVG, ranging & light off) / 50.4W (Stall, ranging & light on)		
Gimbal			
Gimbal Type	3-axis orthogonal Mechanical Stabilization		
Angular Accuracy	±0.01°		
Controllable Range	Pitch: -120°~ 55°, Roll: ±40°, Yaw: ±360° constantly		
Max Controllable Speed	±200°/s		
Zoom Camera			
Image Sensor	1/2.8"CMOS, Effective Pixels: 4.09M		
Lens	Actual Focal Length: 4.7~141mm (Equivalent focal length: 27.8~837mm)		
Resolution	2688 (H) x 1520 (V)		
Pixel Size	2.6µm (H) x 2.6µm (V)		
Optical Zoom Rate	30x	Equivalent Digital Zoom Rate	4x
Thermal Camera			
Thermal Sensor	Uncooled VOx Microbolometer		
Lens	Focal Length: 25mm (Equivalent focal length: 93.2mm)		
Resolution	640 (H) x 512 (V)		
Pixel Size	12µm (H) x 12µm (V)		
Spectral Band	8~14µm	Sensitivity (NETD)	<50mk@F1.0@25°C
Laser Range Finder			
Wavelength	905nm		
Max Laser Power	1mW		
Laser Safety	Class 1M (IEC 60825-1:2014)		
Measurement Accuracy	±0.3m (<300m) / ±1.0m (>300m)		
Measurement Range	5~1800m (φ12m vertical surface with 20% reflectivity)		
Laser Lighting Module			
Wavelength	850±10nm	Beam Diameter	14m±54m@100m
Laser Power	0.8Wx2	Effective Illumination Distance	≤200m
Beam Angle	8°+30°	Laser Safety	Class 3B (IEC 60825-1:2014)
AI Multi-object Detection & Tracking			
Object Identification Size	≥30x20 px	Tracking Deviation Output Delay	≤60ms
Object Identification Rate	≥65%	Target Pixel Error	≤±1px
Object Identification Quantity	≤50	Tracking Speed	>24px / frame
Target Tracking Size	16x16~256x256 px	Target Memory Time	>5s
Tracking Deviation Refresh Rate	30Hz		
Image & Video			
Image Format	JPEG	Video Format	MP4
Maximum Image Resolution	1920 x 1080	Stream Encode Format	H.264, H.265
EXIF	Shooting point coordinate	Stream Network Protocol	RTSP
Maximum Video Resolution	Stream: 1920 x 1080 @25fps, Recording: 1920 x 1080 @30fps		
Storage			
Supported SD Cards	Supports a Speed Class 10 MicroSD card with a capacity of up to 256GB		
Environment			
Operating Temperature	-20°C~50°C		
Storage Temperature	-40°C~80°C		
Operating Humidity	≤85%RH (Non-condensing)		



D-125^{AI}
Intelligent Multi-sensor
Spherical Gimbal

- AI Multi-object Detection & Tracking
- 120x Zoom
- Thermal 640x512 25mm
- Laser Ranging 1800m

MAVLINK
QGroundControl

125mm Sphere Diameter 1055g Total Weight

360°xN Yaw Axis Spins Continually

● Nonorthogonal ● Orthogonality

Spherical Shape 3-axis
Nonorthogonal
Mechanical Stabilized Structure

**FREORLD
BRAND LLC**

General			
Dimensions	142 x 125 x 187mm		
Weight	1055g		
Operating Voltage	20 ~ 53 VDC		
Power	10.7W (Stabic, ranging off) / 40.0W (Peak, ranging on)		
Gimbal			
Gimbal Type	3-Axis Nonorthogonal Mechanical Stabilization		
Angular Accuracy	±0.01°		
Controllable Range	Pitch: -120° ~ 40°, Roll: ±40°, Yaw: ±360° constantly		
Max Controllable Speed	±200°/s		
Zoom Camera			
Image Sensor	1/2.8" CMOS, Effective Pixels: 4.09M		
Lens	Actual Focal Length: 4.7-141mm (Equivalent focal length: 27.9-937mm)		
Resolution	2698 (H) x 1520 (V)		
Pixel Size	2.0µm (H) x 2.0µm (V)		
Optical Zoom Rate	30x		
Equivalent Digital Zoom Rate	4x		
Thermal Camera			
Thermal Sensor	Uncooled VOx Microbolometer		
Lens	Focal Length: 25mm (Equivalent focal length: 93.2mm)		
Resolution	640 (H) x 512 (V)		
Sensitivity (NETD)	<50mk@F1.0@25°C		
Laser Range Finder			
Wavelength	905nm		
Max Laser Power	1mW		
Laser Safety	Class 1M (IEC 60825-1:2014)		
Measurement Accuracy	±0.3m (<300m) / ±1.0m (<300m)		
Measurement Range	5-1800m (φ12m vertical surface with 20% reflectivity)		
AI Multi-object Detection & Tracking			
Object Identification Size	≥30x20 px	Tracking Deviation Output Delay	≤80ms
Object Identification Rate	≥85%	Target Pixel Error	≤±1 px
Object Identification Quantity	≤50	Tracking Speed	>24 px / frame
Target Tracking Size	16x16 ~ 256x256 px	Target Memory Time	>5s
Tracking Deviation Refresh Rate	30Hz		
Image & Video			
Image Format	JPEG	Stream Encode Format	H.264, H.265
Maximum Image Resolution	1920 x 1080	Stream Network Protocol	RTSP
EXIF	Shooting point coordinate		
Video Format	MP4		
Maximum Video Resolution	Stream: 1920 x 1080 @25fps, Recording: 1920 x 1080 @30fps		
Storage			
Supported SD Cards	Supports a Speed Class 10 MicroSD card with a capacity of up to 256GB		
Environment			
Operating Temperature	-20°C ~ 50°C		
Storage Temperature	-40°C ~ 60°C		
Operating Humidity	≤85%RH (Non-condensing)		



D-90^{AI}
Intelligent Multi-sensor
Spherical Gimbal

- AI Multi-object Detection & Tracking
- 30x Zoom
- Thermal 340x512 75mm
- Laser Ranging 1200m

MAVLINK
QGroundControl

96mm Sphere Diameter 608g Total Weight

360°xN Yaw Axis Spins Continually

● Nonorthogonal ● Orthogonality
Spherical Shape 3-axis
Nonorthogonal
Mechanical Stabilized Structure

**FREORLD
BRAND LLC**

General			
Dimensions	96.4 x 96 x 147mm		
Weight	608g		
Operating Voltage	14 - 53 VDC		
Power	10.5W (AVG, ranging off) / 55W (Stall, ranging on)		
Gimbal			
Gimbal Type	3-Axis Nonorthogonal Mechanical Stabilization		
Angular Accuracy	±0.01°		
Controllable Range	Pitch: -150° ~ +50°, Yaw: ±360° constantly		
Max Controllable Speed	Pitch: ±200°/s, Yaw: ±200°/s		
Zoom Camera			
Image Sensor	1/2.8" CMOS; Effective Pixels: 2.07M		
Lens	Focal Length: 4.7-47mm		
Resolution	1920 x 1080		
Pixel Pitch	2.9µm		
Optical Zoom Rate	10x		
Equivalent Digital Zoom Rate	3x		
Thermal Camera			
Thermal Sensor	Uncooled VOx Microbolometer		
Lens	Focal Length: 18mm		
Resolution	640 x 512		
Pixel Pitch	12µm		
Spectral Band	8-12µm		
Sensitivity (NETD)	<50mk@25°C		
Laser Range Finder			
Wavelength	905nm	Measurement Accuracy	±1.0m
Max Laser Power	1mW		
Laser Safety	Class 1M (IEC 60825-1:2014)		
Measurement Range	5-1200m (φ12m vertical surface with 20% reflectivity)		
AI Multi-object Detection & Tracking			
Object Size	16x16 - 126x126 px		
Object Identification Delay	<40ms		
Tracking Speed	±32 px / field		
Tracking Deviation Refresh Rate	30Hz		
Tracking Deviation Output Delay	≤5ms		
Image & Video			
Image Format	JPEG	Maximum Video Resolution	1080P@25fps
Maximum Image Resolution	1920 x 1080	Stream Encode Format	H.264, H.265
EXIF	Shooting point coordinate	Stream Network Protocol	RTSP
Video Format	MP4		
Storage			
Supported SD Cards	Supports a Speed Class 10 MicroSD card with a capacity of up to 256GB		
Environment			
Operating Temperature	-20°C ~ 50°C		
Storage Temperature	-40°C ~ 60°C		
Operating Humidity	≤85%RH (Non-condensing)		



D-90^{DE}
Intelligent Multi-sensor
Spherical Gimbal

- AI Multi-object Detection & Tracking
- 30x Zoom
- Dual-view
- Laser Ranging 1200m

MAVLINK
QGroundControl

96mm Sphere Diameter 576g Total Weight

360°xN Yaw Axis Spins Continually

Nonorthogonal Orthogonality
Spherical Shape 3-axis Nonorthogonal Mechanical Stabilized Structure

**FREORLD
BRAND LLC**

General	
Dimensions	96.4 x 96 x 147mm
Weight	576g
Operating Voltage	14 ~ 53 VDC
Power	10.5W (AVG, ranging off) / 55W (Stall, ranging on)
Gimbal	
Gimbal Type	3-Axis Nonorthogonal Mechanical Stabilization
Angular Accuracy	±0.01°
Controllable Range	Pitch: -150° ~ +50°, Yaw: ±360° constantly
Max Controllable Speed	Pitch: ±200°/s, Yaw: ±200°/s
Zoom Camera	
Image Sensor	1/2.8" CMOS; Effective Pixels: 2.07M
Resolution	1920 x 1080
Pixel Pitch	2.9µm
Optical Zoom Rate	10x
Focal Length	4.7~47mm
Equivalent Digital Zoom Rate	3x
Wide Camera	
Thermal Sensor	1/2.8" CMOS; Effective Pixels: 2.07M
Resolution	1920 x 1080
Pixel Pitch	2.9µm
Focal Length	5.1mm
Laser Range Finder	
Wavelength	905nm
Max Laser Power	1mW
Laser Safety	Class 1M (IEC 60825-1:2014)
Measurement Accuracy	±1.0m
Measurement Range	5~1200m (φ12m vertical surface with 20% reflectivity)
AI Multi-object Detection & Tracking	
Object Size	18x18 ~ 128x128 px
Object Identification Delay	<40ms
Tracking Speed	±32 px / field
Tracking Deviation Refresh Rate	30Hz
Tracking Deviation Output Delay	±5ms
Image & Video	
Image Format	JPEG
Maximum Image Resolution	1920 x 1080
EXIF	Shooting point coordinate
Video Format	MP4
Maximum Video Resolution	1080P@25fps
Stream Encode Format	H.264, H.265
Stream Network Protocol	RTSP
Storage	
Supported SD Cards	Supports a Speed Class 10 MicroSD card with a capacity of up to 256GB
Environment	
Operating Temperature	-20°C ~ 50°C
Storage Temperature	-40°C ~ 60°C
Operating Humidity	≤85%RH (Non-condensing)



D-80 AI
Dual-view
Spherical Gimbal

AI Multi-object Detection & Tracking

30x Zoom

Dual-view

Laser Lighting 200m

MAVLINK
QGroundControl

80mm Sphere Diameter 429g Total Weight

360°xN Yaw Axis Spins Continually

● Nonorthogonal ● Orthogonality

Spherical Shape 3-axis Nonorthogonal Mechanical Stabilized Structure

**FREORLD
BRAND LLC**

General			
Dimensions	85.6 x 86 x 129.3mm		
Weight	429g		
Operating Voltage	14 - 53 VDC		
Power	6.7W (AVG, light off) / 55W (Stall, light on)		
Gimbal			
Gimbal Type	3-Axis Nonorthogonal Mechanical Stabilization		
Angular Accuracy	±0.01°		
Controllable Range	Pitch: -157°~+80°, Yaw: ±360°constantly		
Max Controllable Speed	Pitch: ±200°/s, Yaw: ±200°/s		
Zoom Camera			
Image Sensor	1/2.8" CMOS; Effective Pixels: 2.07M	Pixel Pitch	2.9µm
Lens	Focal Length: 4.7~47mm	Optical Zoom Rate	10x
Resolution	1920 x 1080	Equivalent Digital Zoom Rate	3x
Wide Camera			
Image Sensor	1/2.8" CMOS; Effective Pixels: 2.07M		
Lens	Focal Length: 2.4mm		
Resolution	1920 x 1080		
Pixel Pitch	2.9µm		
Laser Lighting Module			
Wavelength	650±10nm		
Laser Power	0.8W		
Beam Angle	8°		
Beam Diameter	14mm@100m		
Effective Illumination Distance	±200m		
Laser Safety	Class 3B (IEC 60825-1:2014)		
AI Multi-object Detection & Tracking			
Object Size	16x16 ~ 128x128 px		
Object Identification Delay	< 40ms		
Tracking Speed	±32 px / field		
Tracking Deviation Refresh Rate	30Hz		
Tracking Deviation Output Delay	≤5ms		
Image & Video			
Image Format	JPEG	Stream Network Protocol	RTSP
Maximum Image Resolution	1920 x 1080		
EXIF	Shooting point coordinate		
Video Format	MP4		
Maximum Video Resolution	1080P@25fps		
Stream Encode Format	H.264, H.265		
Storage			
Supported SD Cards	Supports a Speed Class 10 MicroSD card with a capacity of up to 256GB		
Environment			
Operating Temperature	-20℃~50℃		
Storage Temperature	-40℃~60℃		
Operating Humidity	≤85%RH (Non-condensing)		

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



D-80^{Pro}
40x-4K
Spherical Gimbal

- 40x Zoom
- 4K 3840 x 2160
- Laser Lighting 200m
- 360°xN Yaw Axis Spins Continually

MAVLINK
QGroundControl

80mm Sphere Diameter 405g Total Weight

360°xN Yaw Axis Spins Continually

● Nonorthogonal ● Orthogonality

Spherical Shape 3-axis Nonorthogonal Mechanical Stabilized Structure



General

Dimensions	85.8 x 86 x 129.3mm
Weight	405g
Operating Voltage	14 ~ 53 VDC
Power	6.7W (AVG, light off) / 55 W (Stall, light on)

Gimbal

Gimbal Type	3-Axis Nonorthogonal Mechanical Stabilization
Angular Accuracy	±0.01°
Controllable Range	Pitch: -157° ~ +80°, Yaw: ±360° constantly
Max Controllable Speed	Pitch: ±200°/s, Yaw: ±200°/s

Zoom Camera

Image Sensor	1/2.8" CMOS, Effective Pixels: 8.29M
Lens	Focal Length: 4.8-48mm
Resolution	3840 x 2160
Pixel Pitch	1.45µm
Electronic Shutter Speed	1 ~ 1/30000 s
Optical Zoom Rate	10x
Equivalent Digital Zoom Rate	4x

Laser Lighting Module

Wavelength	850±10nm
Laser Power	0.8W
Beam Angle	8°
Beam Diameter	14m@100m
Effective Illumination Distance	≤200m
Laser Safety	Class 3B (IEC 60825-1:2014)

Image & Video

Image Format	JPEG
Maximum Image Resolution	3840 x 2160
EXIF	Shooting point coordinate
Video Format	MP4
Maximum Video Resolution	4K@30fps
Stream Encode Format	H.264, H.264H, H.264B, H.265, MJPEG
Stream Network Protocol	ONVIF, RTSP

Storage

Supported SD Cards	Supports a Speed Class 10 MicroSD card with a capacity of up to 256GB
--------------------	---

Environment

Operating Temperature	-20°C ~ 50°C
Storage Temperature	-40°C ~ 60°C
Operating Humidity	≤95%RH (Non-condensing)



General	
Dimensions	59 x 48.4 x 85.7mm
Weight	110g
Operating Voltage	10 ~ 26.4VDC
Power	6.5W (AVG) / 20W (Stall)
Gimbal	
Gimbal Type	3-axis Nonorthogonal Mechanical Stabilization
Angular Accuracy	±0.01°
Controllable Range	Pitch: -135° ~ +100°, Roll: ±50°, Yaw: ±150°
Max Controllable Speed	±200°/s
Fixed Camera	
Image Sensor	1/2.8" CMOS, Effective Pixels: 8.29M
Lens	Actual Focal Length: 6.0mm (Equivalent focal length: 34.4mm)
Resolution	3840 (H) x 2160 (V)
Pixel Size	1.45µm (H) x 1.45µm (V)
Equivalent Digital Zoom Rate	8x
Thermal Camera	
Thermal Sensor	Uncooled VOx Microbolometer
Lens	Actual Focal Length: 10.0mm (Equivalent focal length: 85.5mm)
Resolution	256 (H) x 192 (V)
Pixel Size	12µm (H) x 12µm (V)
Spectral Band	8~14µm
Sensitivity (NETD)	<50mk@25°C
AI Multi-object Detection & Tracking	
Object Size	16x16~126x126 px
Object Identification Delay	<40ms
Tracking Speed	±32px / field
Tracking Deviation Refresh Rate	30Hz
Tracking Deviation Output Delay	≤5ms
Image & Video	
Image Format	JPEG
Maximum Image Resolution	3840x2160
EXIF	Shooting point coordinate
Video Format	MP4
Maximum Video Resolution	Stream: 1920 x 1080 @30fps, Recording: 3840 x 2160 @30fps
Stream Encode Format	H.264, H.265
Stream Network Protocol	RTSP
Storage	
Supported SD Cards	Supports a Speed Class 10 MicroSD card with a capacity of up to 256GB
Environment	
Operating Temperature	-20°C ~ 50°C
Storage Temperature	-40°C ~ 60°C
Operating Humidity	≤85%RH (Non-condensing)



General

Dimensions	59.2 x 48.4 x 80.2mm
Weight	100g
Operating Voltage	10 ~ 26.4VDC
Power	6W (AVG) / 20W (Stall)

Gimbal

Gimbal Type	3-axis Nonorthogonal Mechanical Stabilization
Angular Accuracy	±0.01°
Controllable Range	Pitch: -135° ~ +100°, Roll: ±50°, Yaw: ±150°
Max Controllable Speed	±200°

Fixed Camera

Image Sensor	1/1.8" CMOS; Effective Pixels: 4.08M
Lens	Actual Focal Length: 8.5mm (Equivalent focal length: 34.8mm)
Resolution	2688 (H) x 1520 (V)
Pixel Size	2.9µm (H) x 1520 (V)
Equivalent Digital Zoom Rate	6x

AI Multi-object Detection & Tracking

Object Size	16x16 ~ 128x128 px
Object Identification Delay	<40ms
Tracking Speed	±32px / field
Tracking Deviation Refresh Rate	30Hz
Tracking Deviation Output Delay	≤5ms

Image & Video

Image Format	JPEG
Maximum Image Resolution	2688 x 1520
EXIF	Shooting point coordinate
Video Format	MP4
Maximum Video Resolution	Stream: 1920 x 1080 @30fps, Recording: 2688 x 1520 @30ps
Stream Encode Format	H.264, H.265
Stream Network Protocol	RTSP

Storage

Supported SD Cards	Supports a Speed Class 10 MicroSD card with a capacity of up to 256GB
--------------------	---

Environment

Operating Temperature	-20°C ~ 50°C
Storage Temperature	-40°C ~ 60°C
Operating Humidity	≤85%RH (Non-condensing)



General

Dimensions	50.2 x 48.4 x 67.4mm
Weight	69g
Operating Voltage	10 ~ 26.4VDC
Power	4.5W (AVG) / 18W (Stall)

Gimbal

Gimbal Type	3-axis Nonorthogonal Mechanical Stabilization
Angular Accuracy	±0.01°
Controllable Range	Pitch: ±120°, Roll: ±60°, Yaw: ±180°
Max Controllable Speed	±200°/s

Fixed Camera

Image Sensor	1/2.8"CMOS; Effective Pixels: 8.29M
Lens	Actual Focal Length: 6.0mm (Equivalent focal length: 34.4mm)
Resolution	3840 (H) x 2160 (V)
Pixel Size	1.45µm (H) x 1.45µm (V)
Equivalent Digital Zoom Rate	8x

AI Multi-object Detection & Tracking

Object Size	16x16 ~ 128x128 px
Object Identification Delay	<40ms
Tracking Speed	±32px / field
Tracking Deviation Refresh Rate	30Hz
Tracking Deviation Output Delay	≤5ms

Image & Video

Image Format	JPEG
Maximum Image Resolution	3840 x 2160
EXIF	Shooting point coordinate
Video Format	MP4
Maximum Video Resolution	Stream: 1920 x 1080 @30fps, Recording: 3840 x 2160 @30ps
Stream Encode Format	H.264, H.265
Stream Network Protocol	RTSP

Storage

Supported SD Cards	Supports a Speed Class 10 MicroSD card with a capacity of up to 256GB
--------------------	---

Environment

Operating Temperature	-20°C~50°C
Storage Temperature	-40°C~80°C
Operating Humidity	≤85%RH (Non-condensing)



XR ROBOTICS

RC Car/ Fixed-wing FPV/
Scale Model Aircraft...

50 x 46.5 x 53mm

C-20 FPV Gimbal
New Stabilization Experience

Magnesium 46g

Compatible With Various
Image Transmission Kits
DJI Vista Walksnail Avatar
DJI O3 Walksnail Moonlight

Fear No Shaking

3-Axis Head Tracking Control

**FREORLD
BRAND LLC**

C-20T 3-Axis FPV Gimbal



General	
Dimensions	46.8 x 46.4 x 53.4mm
Weight	48g
Operating Voltage	7.4-26.4VDC
Power	1.5W (AVG) / 14W (Stall)
Mounting	Downward / Upward
Control Port	UART (private protocol / MAVLink) / PWM / S.BUS
Gimbal	
Gimbal Type	3-axis Nonorthogonal Mechanical Stabilization
Angular Accuracy	±0.005°
Controllable Range	Pitch: ±120°, Roll: ±60°, Yaw: ±160°
Max Controllable Speed	±1500°/s
Camera Suitability	
Maximum Weight	20g
Maximum Width	19mm

C-20D 2-Axis FPV Gimbal



General	
Dimensions	46.7 x 46.5 x 26.2mm
Weight	30g
Operating Voltage	7.4-26.4VDC
Power	1.2W (AVG) / 9.5W (Stall)
Mounting	Downward / Upward
Control Port	UART (private protocol / MAVLink) / PWM / S.BUS
Gimbal	
Gimbal Type	2-axis Mechanical Stabilization
Angular Accuracy	±0.005°
Controllable Range	Pitch: ±120°, Roll: ±60°
Max Controllable Speed	±1500°/s
Camera Suitability	
Maximum Weight	20g
Maximum Width	19mm

C-20S Single-Axis FPV Gimbal



General	
Dimensions	33.8 x 38 x 20.5mm
Weight	17g
Operating Voltage	7.4-26.4VDC
Power	1.0W (AVG) / 5.5W (Stall)
Mounting	Downward / Upward
Control Port	UART (private protocol / MAVLink) / PWM / S.BUS
Gimbal	
Gimbal Type	Single-axis Mechanical Stabilization
Angular Accuracy	±0.005°
Controllable Range	Pitch: ±120°
Max Controllable Speed	±1500°/s
Camera Suitability	
Maximum Weight	20g
Maximum Width	19mm



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace FreeWorldImports.com

Additionally, explore our featured listings in the **UAV & REMOTE TECHNOLOGY** section of our marketplace under **Gimbals, Night Vision Pods, Autonomous Formation Drones, and Multi-Sensor Pods.**

We also have a variety of UAVs that are not listed within the marketplace.

Interested in more options? [Email us](#) for details on both listed and unlisted UAV products and solutions.

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace FreeWorldImports.com

OTHER FREEWORLD INVENTORY LIQUIDATION SERVICES OFFERINGS

Please click on the image or the associated hyperlink to learn more



[FWB – SPECIAL DEALS COMMODITIES WEBSTORE](#)

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace FreeWorldImports.com

Please click on the image or the associated hyperlink to learn more



[SOURCE YOUR PRODUCTS HERE | DELIVERED DUTY PAID \(DDP\)](#)

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace FreeWorldImports.com

Please click on the image or the associated hyperlink to learn more



DEPARTMENT STORES MIXED BUNDLES FOR BIG SAVINGS

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace [FreeWorldImports.com](https://freeworldimports.com)

Please click on the image or the associated hyperlink to learn more



[FWI FEATURED SUPPLIERS](#)

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | **Liquidation Marketplace:** <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | **Email:** bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace FreeWorldImports.com

Please click on the image or the associated hyperlink to learn more



24 X 7 X 365 NON-AUCTION DEALS

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace FreeWorldImports.com

Please click on the image or the associated hyperlink to learn more

FWI LIQUIDATION MARKETPLACE AFFILIATE PROGRAM

Become an **ONLINE INVENTORY LIQUIDATOR** using the FWI link based model which enable you to create links to any product within the FWI Marketplace. You have the ability to share these links with potential customers via email, social media and other digital mediums. You will **earn between two to five percent (2% - 5%) commission on the sales of products** which are sold based on your efforts. These links contains identifiers that will ensure that you receive compensation when a purchase is made on a linked item containing your identifier. There are no charges associated with this groundbreaking business opportunity, your participation will not cost you a dime, it is completely free of charge.

Online Inventory Liquidation Marketplace



Buying Platform
<https://www.freeworldimports.com/>
609-318-0570
bizdev@freeworldimports.com

ONLINE INVENTORY LIQUIDATOR REGISTRATION

[FWI AFFILIATE PROGRAM](#)

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace [FreeWorldImports.com](https://freeworldimports.com)

Please click on the image or the associated hyperlink to learn more



[FWI SUPPLIER ENGAGEMENT](#)

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace FreeWorldImports.com

Please click on the image or the associated hyperlink to learn more

An advertisement for HSBLCO Solution. At the top, there is a dark red banner with the "VPOS" logo on the left and the "HSBLCO SOLUTION" logo on the right. Below the banner, the text "DELIVERING VALUE TO CALL CENTERS AND BEYOND INTEGRATED" is in a smaller font, followed by "VIRTUAL POINT OF SALE SOLUTION" in a large, bold, dark red font. The central image shows a smiling woman with dark hair wearing a headset, with her hands held out in a gesture. At the bottom of the advertisement, the URL "www.sasapplication.com/webapplication" is displayed. The background of the advertisement features a large, faint watermark of the letters "VPOS".

www.sasapplication.com/webapplication

CLOUD BASED SOLUTIONS FOR FORWARD LOOKING ORGANIZATIONS

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace FreeWorldImports.com

Please click on the image or the associated hyperlink to learn more



PINK LABELED WOMEN'S URBAN APPAREL

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | Liquidation Marketplace: <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | Email: bizdev@freeworldbrand.com



Global Traders: Operators of the Unconventional Inventory Liquidation Marketplace FreeWorldImports.com

FOR MORE INFORMATION FREEWORLD LIQUIDATION SERVICES

A Service of FreeWorld Brand, LLC



Phone: +1-609-256-9162

Email: bizdev@freeworldimports.com
bizdev@freeworldbrand.com

309 Fellowship Road | East Gate Center | Suite 200 | Mt. Laurel | NJ 08054

Web-Presence: <http://freeworldbrand.com> | **Liquidation Marketplace:** <https://freeworldimports.com>

Commodities Webstore: <https://commodities.freeworldbrand.com/>

Phone/Fax: 609-256-9162 | **Email:** bizdev@freeworldbrand.com