








**ANTI-COVID19 PRODUCT - READY STOCK AS 09/10/2020  
DUBAI, UAE & KARACHI, PAKISTAN**

Sl. No	Item name	IMAGES	Quantity(in pcs)
<b>Located in DUBAI</b>			
1	3PLY Surgical Mask		1000000
2	Isolation Gown		10000
3	White full cover Isolation Gown		150000
<b>Located in PAKISTAN</b>			
1	3 PLY Surgical Masks		1000000
2	Medical Isolation Gown Level 3		100000
3	Isolation Gown		30000
4	White full cover Isolation Gown		100000

## CERTIFICATIONS & OTHER RELATED DOCUMENTATION

### 3 PLY SURGICAL MASK EAR LOOP

#### MEDICAL FACE MASK TESTS AND REQUIREMENTS

U.S.A.: ASTM F2100-19 STANDARD SPECIFICATION FOR PERFORMANCE OF MATERIALS USED IN MEDICAL FACE MASKS  
EUROPE: EN 14683:2019 MEDICAL FACE MASKS – REQUIREMENTS AND TEST METHODS

		ASTM F2100-19			EN 14683:2019 Barrier Levels		
		Level 1	Level 2	Level 3	Type I	Type II	Type IIR
Barrier Testing	BFE % ASTM F2301, EN 14683	≥95	≥98	≥99	≥95	≥98	
	PFE % ASTM F2299	≥95	≥98		Not required		
	Synthetic Blood ASTM F1882, ISO22809	Pass at 80 mmHg	Pass at 120 mmHg	Pass at 160 mmHg	Not required	Pass at: 2.10.0 40Pa (1.136 mmHg)	
Physical Testing	Differential Pressure EN 14683	<5.0 mmHg/cm <sup>2</sup>	<6.0 mmHg/cm <sup>2</sup>		<40 Pa/cm <sup>2</sup>	<60 Pa/cm <sup>2</sup>	
Safety Testing	Flammability 16 CFR Part 1610	Class 1 (≥ 3.5 seconds)			See European Medical Directive (2007/47/EC, MDD 93/42/EEC)		
	Microbial Cleanliness ISO 11737-1	Not required			≤30 cfu/g		
	Biocompatibility ISO 10993	510 K Guidance recommends testing to ISO 10993			Complete an evaluation according to ISO 10993		
Sampling ANSI/ASQC Z1.4 ISO 2859-1		<ul style="list-style-type: none"> <li>AQL 4% for BFE, PFE, Delta P</li> <li>32 masks for Synthetic Blood (Pass = ≥29 passing, Fail = ≤28 passing)</li> <li>14 masks for Flammability</li> </ul>			<ul style="list-style-type: none"> <li>Minimum of 5 masks up to an AQL of 4% for BFE, Delta P and Microbial Cleanliness.</li> <li>32 masks for Synthetic Blood (Pass = ≥29 passing, Fail = ≤28 passing)</li> </ul>		



**Model # MMS-17786**

**Features:**  
Easy Breathing  
100% Latex Free  
soft, Rounded Ear Loop,  
Form-fitting, pliable nose band  
Comfortable Inner lining  
for facial comfort  
BFE over 98%

**Mask Measurement**  
Length = 175mm  
Width = 95 mm

**Packing :**  
50 pcs x 1 Pkt  
40 pkt x 1 carton

**Made in Pakistan**

**FDA APPROVED  
D404309**



**ENGAGE THE HYPERLINKS BELOW FOR ADDITIONAL INFORMATION**

1. [Test reports \(Standard: ATSM F2100-19 \(Level 3\)\)](#)
2. [FDA – Certificate of Registration](#)

**Disposable  
Coverall 40 gsm**

Disposable coveralls are an item of personal protective equipment (PPE) designed to cover the whole body and other clothing to protect against dirt or other outside contaminants. Coveralls are one piece and loose fitting for ease of movement, with sleeves, full leggings and often a hood to cover the head.



**Model # SG-2526**



**Measurement  
66\*34\*42  
Packing :  
50 pcs x 1 carton  
Weight : 11 kg**



**ENGAGE THE HYPERLINKS BELOW FOR ADDITIONAL INFORMATION**

1. [Test reports – 40 GSM Gown](#)
2. [FDA – Certificate of Registration](#)

**Disposable Isolation Gown**

**American Safety®**

EN13688:2013 **Model # SG-2526**



**FDA APPROVED**

**Disposable Gown**  
40 gsm  
EN13688 (level-I)

**MADE IN PAKISTAN**



**Measurement**  
66X40X48 CM  
**Packing :**  
100 pcs x 1 carton  
**Weight : 14 kg**



DISPOSABLE ISOLATION GOWN  
QUANTITY: 100 PCS  
COLOR: BLUE  
SIZE: 66X40X48 CM  
MADE IN PAKISTAN

**ENGAGE THE HYPERLINKS BELOW FOR ADDITIONAL INFORMATION**

1. [Test report – 40GSM Gown –Level 1](#)
2. [FDA – Certificate of Registration](#)

**MEDICAL GOWN**



**EN13688:2013  
AAMI LEVEL III**

**Model # SG-1211**



**Measurement  
66X40X48 CM  
Packing :  
100 pcs x 1 carton  
Weight : 21 kg**



**GSM : 60 gsm  
COLOR : SKY BLUE  
FABRIC : POLYLEMINATED  
MATERIAL : POLYPROPYLENE  
CONSTRUCTION : SPUNBOND  
CATEGORY : PRC - SCP**



**Hydrostatic Head Pressure Test**

AATCC 127:2003

Area 100 cm<sup>2</sup>

Tested Side = Face

Temperature = 21.0°C

Specimen 1	52 cm of water
Specimen 2	54 cm of water
Specimen 3	56 cm of water
Average:	54 cm of water

Client's Requirement: ANSI/AAMI PB 70:2012  
Level 3: ≥50cm

**ENGAGE THE HYPERLINKS BELOW FOR ADDITIONAL INFORMATION**

1. [Test reports - 60GSM Gown](#)
2. [FDA – Certificate of Registration](#)

## MICROPOROUS COVERALL TYPE 5/6 Protection

**EN13034:2005+A1:2009**  
**Model # MP-1211**

TYPE 5-B

TYPE 6-B

EN 14126

EN 1149-5

EN 1073-2

Type 5		EN 14000	Liquid tight protective coveralls (Type 5)
Type 6		EN 14000	Spray tight protective coveralls (Type 6)
Type 4		EN 14000	Particle tight protective coveralls (Type 4)
Type 3		EN 14000	Limited droplet protective coveralls (Type 3)

**Popular Uses:**  
Agriculture  
Biological Protection  
Construction  
Food Processing  
Mining  
Oil & Gas Industries  
Pharmaceutical

**Features:**  
Multi Layer Barrier  
Class 3 resistant to penetration by liquid  
Class 2 tensile and puncture resistance  
Optimum strength and tear resistant  
Highly durable and lightweight  
Optimized bodyfit  
Effective barrier to both inorganic chemical and biological hazard

**Measurement**  
50\*30\*38  
**Packing :**  
50 pcs x 1 carton  
**Weight : 11 kg**

60 gsm



---

## ENGAGE THE HYPERLINKS BELOW FOR ADDITIONAL INFORMATION

1. [Test reports - Microporous 60GSM Gown – Type 6](#)
  2. [Test reports - Microporous Gown – Type 5](#)
  3. [FDA – Certificate of Registration](#)
- 

## FOR MORE INFORMATION



## Contact Information

**Phone:** +1609-318-0570

**Email:** [bizdev@freeworldimports.com](mailto:bizdev@freeworldimports.com)

### ABOUT FREEWORLD BRAND, LLC.

FREEWORLD, BRAND, LLC - Global Traders & Merchants: Operators of the online marketplaces [FREEWORLDIMPORTS](#) and [FREEWORLDEXPORTS](#)